


1-951 Silicone Remover

APPLICATION DATA



Mixing Ratio : Non applicable.




Application viscosity : Airspray (sec) : -
DINCUP 4mm/20°C : Pressure tank (sec) : -
 : Airless (sec) : -



	<u>Nozzle diameter (mm)</u>	<u>Spraying pressure (bar)</u>
Gravity feed	-	-
Suction feed	-	-
Pressure tank	-	-
Airless	-	-
HVLP	-	See Info Manufacturer
HE	-	See Info Manufacturer



Spray coats / Layer thickness : - / -
 (μm)



Flash-off (min) : 20°C : -



Drying time (min) : 20°C : -
 : 60°C Obj. : -



Potlife (min) : 20°C : -

1-951 Silicone Remover



PRODUCT INFO

- Area of application** : Silicon Remover for old lacquer layers and hardening through new lacquer layers.
- Chemical base** : Mix of organic solvents and thinners.
- General qualities** : Standard Silicon Remover.
- Auxiliary materials** : Non applicable.

EU regulations

- VOC code** : 2004/42/IIB(a)(850)(759)
- Product Subcategory (according directive 2004/42/EC) and max. VOC content (ISO 11890-1/2) of the ready to use product** : IIB/a. Preparatory and cleaning - Preparatory. EU limit values: 850g/l. (2007) This product contains a maximum of 759 g/l VOC.

Physical properties	Specific gravity (kg/l)	: 0.792
	Flash point	: Closed cup: 9°C (48.2°F)
	Vol.% solids	: 0
	Economy	: -
	Gloss	: -
	Colour	: Clear.

- Substrates** : Steel, old and new lacquer layers.
- Undercoats** : n/a
- Finishing materials** : n/a
- Cleaning the equipment** : -
- Storage life (years)** : min. 2
(Under normal storage conditions and unopened tins).