



# WATERBASED ANTI-STATIC DEGREASER 90-851

## APPLICATION DATA



Mixing Ratio : Ready to Use




Application-Viscosity : Soak a clean cloth with 90-851, then wipe surface. Then, wipe dry with a clean cloth before product dries. **DO NOT ALLOW** 90-851 to dry on the surface. If this occurs, re-apply 90-851 using a clean cloth and wipe dry.  
@ 20°C/70°F  
DIN Cup 4 mm



		<u>Nozzle diameter</u>
:	Gravity feed	N/A
:	Suction feed	N/A
:	HVLP/LVLP	N/A



Spray Coats/ Film Thickness : N/A



Flash-off : N/A



:	<u>20°C/70°F</u>	<u>60°C/140°F (object temperature)</u>
:	N/A	N/A



Potlife\* : N/A  
@ 20°C/70°F

# ***WATERBASED ANTI-STATIC DEGREASER 90-851***

<b>Field of application</b>	: Multi-Purpose water-base cleaner for use in initial and final surface prep.
<b>Chemical basis</b>	: Water and solvents.
<b>General qualities</b>	: Cleaner with anti-static properties
<b>Auxiliary materials</b>	: Not applicable
<b>Mixing ratio (volume)</b>	: Ready-to-use
<b>Physical properties</b>	
Density	: 8.32 lbs/gal
Flashpoint	: Closed cup: 175°F (79°C)
Weight % Volatiles	: 99.5%
Weight % Water and/or Exempts	: 97.1%
Actual VOC	: 0.2 lbs./gal. (24 g/L)
<b>Gloss</b>	: N/A
<b>Substrates</b>	: OEM Finishes, Refinish undercoats, Aluminum, Bare Metal, and Plastics
<b>Cleaning the Equipment</b>	: N/A
<b>Colour</b>	: Clear.
<b>Storage life</b>	: Under normal storage conditions for up to two years (unopened container).