



J. Stöver / ws

Telefon

+49 (71 54) 8 11-4 52

Telefax

+49 (71 54) 8 11-1 90

eMail

Joern.Stoever@sata.com

Datum

25. Mai 2012

To Whom It May Concern

It is our pleasure to confirm that the following SATA spray guns do comply with HVLP mandates; namely that they show maximum 10 psi air cap pressure at recommended spray gun inlet pressure highlighted in the operating manuals. The transfer efficiency of all listed SATA HVLP spray guns is larger 65 % provided the spray gun is set-up by the user with the recommended inlet pressure and spray distance shown in the operating manuals.

SATA® MC-B/N/HVLP	maximum spray gun inlet pressure:	43 psi
SATAjet® B NR 95 HVLP	maximum spray gun inlet pressure:	43 psi
SATAjet® K NR 95 HVLP	maximum spray gun inlet pressure:	43 psi
SATAjet® H NR 95 HVLP	maximum spray gun inlet pressure:	43 psi
SATAminijet® NR	maximum spray gun inlet pressure:	43 psi
SATAminijet® 2 HVLP	maximum spray gun inlet pressure:	29 psi
SATAminijet® 3 HVLP	maximum spray gun inlet pressure:	29 psi
SATAminijet® 4 HVLP	maximum spray gun inlet pressure:	29 psi
SATAminijet® 3000 B HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 2000 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 2000 HVLP DIGITAL® 2	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 HVLP DIGITAL®	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 B HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 B HVLP DIGITAL®	maximum spray gun inlet pressure:	29 psi
SATAjet® 4000 B HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 4000 B HVLP DIGITAL®	maximum spray gun inlet pressure:	29 psi
SATAjet® K3™ HVLP	maximum spray gun inlet pressure:	36 psi
SATAjet® K3™ HVLP DIGITAL®	maximum spray gun inlet pressure:	36 psi
SATAjet® 3000 K™ HVLP	maximum spray gun inlet pressure:	36 psi
SATA® KLC™ HVLP	maximum spray gun inlet pressure:	29 psi
SATA® LM™ 2000 B HVLP	maximum spray gun inlet pressure:	43 psi
SATA® LM™ 2000 H HVLP	maximum spray gun inlet pressure:	43 psi
SATA® LM™ 2000 K HVLP	maximum spray gun inlet pressure:	43 psi
SATA® LP90™ jet NR95™ HVLP	maximum spray gun inlet pressure:	48 psi
SATA® LP90™ ROB jet NR95™ HVLP	maximum spray gun inlet pressure:	48 psi
SATA® LP™ jet K3™ HVLP	maximum spray gun inlet pressure:	58 psi
SATA® LP™ jet K3™ HVLP ROB™	max. round air inlet pressure:	42 psi
	max. flat air inlet pressure:	48 psi
SATAjet® 3000 A™ HVLP	maximum spray gun inlet pressure:	58 psi
SATAjet® 3000 ROB™ HVLP	max. round air inlet pressure:	42 psi
	max. flat air inlet pressure:	48 psi
SATAminijet® 3000 A HVLP	maximum spray gun inlet pressure:	33 psi
SATAminijet® 3000 A S HVLP	maximum spray gun inlet pressure:	22 psi
SATAjet® 90-2 HVLP	maximum spray gun inlet pressure:	29 psi



SATAjet® 1000 K™ HVLP
SATAjet® 100 B F HVLP
SATAjet® 1000 B HVLP

maximum spray gun inlet pressure: 36 psi
maximum spray gun inlet pressure: 29 psi
maximum spray gun inlet pressure: 29 psi

SATA GmbH & Co. KG
R&D Department



i. V. Dr. Ewald Schmon



i. V. Jörg Göttling